

# Anybus X-gateway – AB7810



## Profibus Master - CC Link Slave

The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.



The Anybus-M Profibus-DP interface supports connection of up to 125 slaves at baudrates up to 12 Mbit/s. The Profibus configuration is defined with NetTool-PB, the windows based configuration software for Profibus from HMS (purchased as a separate accessory). The Profibus interface module is certified by the Profibus user organization and has proven conformance and interoperability with leading manufacturers of I/O, drives, instruments etc Configuration is downloaded to the module via the RS232 configuration port.

The CC-Link interface is a slave module for the CC-Link fieldbus system. It contains all the functionality needed to turn an application into a complete CC-Link remote device and it is configured to use the generic PLC profile. The CC-Link interface module is certified by the CLPA organisation and has proven conformance and interoperability with leading PLC's, HMI's etc

### KEY FEATURES

- Profibus configuration: NetTool-PB for Windows
- Built on Siemens ASIC ASPC2 Step E with Infineon C165

#### Microprocessor

- Up to 125 slaves can be connected
- Profibus configuration through RS232 configuration port
- Supports PA baud rate 45.45 kbit/s
- Uses up to 4 occupied stations on CC-Link - configurable size
- Uses the CC-Link PLC profile for data exchange
- Complete Profibus DP Master according to IEC 61158

### TECHNICAL SPECIFICATIONS

Size:	126 mm x 110 mm x 42 mm
Power Supply:	24 VDC (±10%)
Temperature:	0-65°C
Current Consump:	max 300 mA
I/O Input:	Default 20 bytes, max 64 bytes (max 128 I/O-points and 16 words on CC-Link)
I/O Output:	Default 20 bytes, max 64 bytes (max 128 I/O-points and 16 words on CC-Link)
Mech Rating:	IP20/Nema1
Config Method:	Windows Hyper Terminal
UL certification:	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4

ATEX certification: ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03

---

Power supply connector: 2-pole 5.08 mm Phoenix pluggable screw connector

---

Profibus baudrate: 9600 bit/s - 12 Mbit/s

---

Profibus address: Node address 0-125

---

Profibus connector: D-sub 9-pin female

---

Accessory order code: 018330 (NetTool-PB configuration tool for Profibus)

---

CC-Link baudrate: 156kbps to 10Mbps

---

CC-Link address: Station 1-64

---

CC-Link connector: 5-pole 5.08 mm Phoenix pluggable screw connector

---

CC-Link config: Configured by CC Link Master via CSP Config file  
(provided by HMS)

---

Price Group: C

---

Order Code: AB7810

---