

Anybus X-gateway – AB7620

Modbus RTU Slave - Modbus Plus Slave

The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.



The Modbus RTU Slave interface is implemented according to Modbus Protocol ref guide (PI-MBUS-300). All data is mapped to 3x and 4x Modbus areas meaning the Input Status and Output Register Word areas. The Modbus RTU standard baudrate is 19200 Bit/s but can be modified on the gateway between 1200 Bit/s to 57 600 Bit/s.

The Modbus Plus interface is based on licensed chip-set and software from Modicon Inc. Supporting both the Global Database and Register mapping to 3x and 4x registers this module implements a versatile Modbus Plus interface. The Modbus Plus interface module is certified by the Modconnect and has proven conformance and interoperability with leading PLC's, HMI's etc

KEY FEATURES

- Supported Modbus RTU functions: 1, 2, 3, 4, 5, 6, 8, 15, 16, 22, 23
- Modbus Plus Global Data Base Transaction, Point-to-Point commands, Read holding registers, Preset single register
- Modbus Plus Host Firmware Rev. 77
- Modbus RTU transmission media RS485

TECHNICAL SPECIFICATIONS

Size:	126 mm x 110 mm x 42 mm
Power Supply:	24 VDC (±10%)
Temperature:	0-65°C
Current Consump:	max 300 mA
I/O Input:	Default 20 bytes, max 512 bytes (max 64 bytes as Modbus Plus Global Data)
I/O Output:	Default 20 bytes, max 512 bytes (max 64 bytes as Modbus Plus Global Data)
Mech Rating:	IP20/Nema1
Config Method:	Windows Hyper Terminal
UL certification:	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
ATEX certification:	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
Power supply connector:	2-pole 5.08 mm Phoenix pluggable screw connector
Modbus RTU baudrate:	1200 Bit/s to 57 600 Bit/s
Modbus RTUNode address	1-247

address:

Modbus RTU
connector: D-sub 9-pin female

Modbus Plus
baudrate: 1 Mbit/s

Modbus Plus address: Node-ID and Source-ID 1-64

ModbusPlus
connector: D-sub 9-pin female

Price Group: C

Order Code: AB7620