

Key Attributes:

- ✓ Most applicable when clearance is an issue.
- ✓ Medium to lower "Air Current Depth". These fans will create horizontal movement from the floor to about 4ft. above the floor.
- ✓ Air speed off of the fan is at MacroAir maximum, forcing air into hard to reach areas, like underneath mezzanines.
- ✓ Excellent for drying floors.
- ✓ Anodized Protected Blades are Corrosion-Resistant.
- ✓ Improves Employee Comfort and Harmony in the Work Place.
- ✓ Highly Energy Efficient, Quiet, and Non-disruptive.
- ✓ Operates for Pennies an Hour.
- ✓ Safe Ergonomic Placement Promotes Clutter Free Work Spaces.
- ✓ Eliminates Need for Small Inefficient High Speed Floor or Desk Fans.
- ✓ Quick ROI.

Basic Specs		
Maximum Speed		119 RPM
Power Usage		.678 KW
Maximum Effective Area		7,000 SQ/FT
Typical Industrial Spacing		55 FT
Mounting Hardware		
Standard		Universal I-Beam Clamp w/ Swivel Joint and 1 Ft Drop
Motor Control Panel (MCP)		
Enclosure		500 x 400 x 210mm, IP44
Variable Frequency Drive (VFD)		Eurotherm
Fuse Block and Fuses		10 Amp
Disconnect Switch		10 Amp, Lockable
Input Power		3Ø 380-460V, 50Hz
Warranty		
Motor and Gearbox		3 YRS
All Other Components		Lifetime
Labour Allowance to Remove & Replace	e in 1 st Year	
	ACP&D Limited Units 6 & 9A, Charlestown Industrial Estate, Robinson Street, Ashton-under-Lyne, Lancashire, OL6 BNS.	QÊ

44 (0)161 343 1884 +44 (0)161 339 0650 ww.acpd.com 8 v.acpd.co.u

