

Anybus X-gateway – AB7663

DeviceNet Scanner/Master - Profibus Slave

The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.



The Profibus DP/DPV1 slave interface is implemented according to the standard IEC61158 as a modular slave, supporting all standard functionality such as Watchdog, Sync and Freeze and diagnostics. Standard DP as well as DPV1 acyclic data services (Class1/Class2) are supported. The Profibus interface module is certified by the Profibus user organization and has proven conformance and interoperability with leading PLC's, HMI's etc. Profibus address is set via rotary switches 0-99.

The DeviceNet Master interface can act both as a Master/Scanner and/or Adapter/Slave. The entire DeviceNet protocol is implemented into the module. The module manages control of up to 63 DeviceNet slaves. Full DeviceNet configuration can be defined and loaded into the Anybus-M module via the HMS configuration software NetTool-DN (purchased as a separate accessory) or via Rockwell's RSNetWorx.

KEY FEATURES

- Complete DeviceNet 2.0 scanner implementation according to ODVA
- DeviceNet Group 2 Client/Server / UCMM support
- Manages up to 63 DeviceNet slaves
- DeviceNet Configuration via AnyBus NetTool-DN or RSNetworx
- DeviceNet Explicit peer to peer messaging, configuration consistency value. I/O Slave messaging: Bit strobe, Polling, Cyclic & Change of State (COS)
 - Watchdog support
 - Sync and Freeze
 - Supports PA baud rate 45.45 kbit/s
- Complete Profibus DP and DPV1 (Class1/Class2) slave functionality according to IEC 61158

TECHNICAL SPECIFICATIONS

Size: 126 mm x 110 mm x 42 mm

Power Supply: 24 VDC ($\pm 10\%$)

Temperature: 0-65°C

Current Consump: max 300 mA

I/O Input: Default 20 bytes, max 512 bytes

I/O Output: Default 20 bytes, max 512 bytes

Mech Rating: IP20/Nema1

Config Method: Windows Hyper Terminal, NetTool-DN or RS-

Networx, EDS and GSD file

UL certification: E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP
A, B, C, D, Temp Code T4

ATEX certification: ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03

Power supply
connect: 2-pole 5.08 mm Phoenix pluggable screw connector

Profibus baudrate: 9600 bit/s - 12 Mbit/s autodetect

Profibus address: Node address 0-99

Profibus connector: D-sub 9-pin female

Profibus config: Configured by Profibus Master via GSD file
(provided by HMS)

DeviceNet baudrate:: 125-500 kbit/s

DeviceNet MacID: 0-63

DeviceNet connector: 5-pole 5.08 mm Phoenix pluggable screw connector

Accessory order018020 (NetTool-DN configuration Tool for
code: DeviceNet)

Price Group: B

Order Code: AB7663