

## Anybus X-gateway – AB7804



### Profibus Master - FIP Slave

The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.



The Anybus-M Profibus-DP interface supports connection of up to 125 slaves at baudrates up to 12 Mbit/s. The Profibus configuration is defined with NetTool-PB, the windows based configuration software for Profibus from HMS (purchased as a separate accessory). The Profibus interface module is certified by the Profibus user organization and has proven conformance and interoperability with leading manufacturers of I/O, drives, instruments etc Configuration is downloaded to the module via the RS232 configuration port.

The FIPIO interface is based an embedded AnyBus-S module proving industrial performance and quality. FIPIO station address can be selected via switches on the end side of the module. A transformer connection on the module provides a isolated fieldbus interface.

### KEY FEATURES

- Profibus configuration: NetTool-PB for Windows
- Built on Siemens ASIC ASPC2 Step E with Infineon C165

#### Microprocessor

- Up to 125 slaves can be connected
- Profibus configuration through RS232 configuration port
- Supports PA baud rate 45.45 kbit/s
- Supports both FIP and WorldFIP standards
- FIPIO profile FEDP (Extended Device Profile), class 0
- Transformer isolated FIP interface
- Complete Profibus DP Master according to IEC 61158

### TECHNICAL SPECIFICATIONS

Size: 126 mm x 110 mm x 42 mm

Power Supply: 24 VDC ( $\pm 10\%$ )

Temperature: 0-65°C

Current Consump: max 300 mA

I/O Input: Default 20 bytes, max 64 bytes

I/O Output: Default 20 bytes, max 64 bytes

Mech Rating: IP20/Nema1

Config Method: Windows Hyper Terminal

UL certification: E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP  
A, B, C, D, Temp Code T4

ATEX certification: ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03

Power supply 2-pole 5.08 mm Phoenix pluggable screw connector

connector:

---

Profibus baudrate: 9600 bit/s - 12 Mbit/s

---

Profibus address: Node address 0-125

---

Profibus connector: D-sub 9-pin female

---

Accessory order  
code: 018330 (NetTool-PB configuration tool for Profibus)

---

FIPIO baudrate: 1 Mbit/s

---

FIPIO address: Node address 0-99

---

FIPIO connector: D-sub 9-pin male

---

Price Group: C

---

Order Code: AB7804

---